This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

25

1	<u>*'</u> 、	1.	A projection display system, comprising:
W	100	(a)	a light source; 36
Ŋ	5	(b)	at least one polarizer; 3840
		(c)	at least one liquid crystal panel for
			generating an image;
		(d)	a projection source for projecting said (48,09)
			image; and
	10	(e)	a polarization compensator having a
			plurality of regions each having a
			respective birefringence, said
# TI			birefringence of at least one of said
. 1			regions being different than said
	15		birefringence of another of said regions.
t.≓ b.÷		2.	The projection display of claim 1 wherein
		said regions a	re arranged in a rectangular matrix. (Fy 5
B 14	20	3.	The projection display of claim 1 wherein
ļ.			re arranged concentrically.
Li		bara regions a	re arranged concentration.

- The projection display of claim 1 having 4. more than two regions.
 - The projection display of claim 1 wherein said polarization compensator is a transmissive liquid crystal device.
- The projection display of claim 5 wherein 30 at least one of said regions has a director orientation that is different than another director orientation of another of said regions.
- The projection display of claim 1, further 35 comprising an analyzer, and said polarization compensator is located between said polarizer and said analyzer.

20

- 8. The projection display of claim 1 wherein said polarization compensator is located at an aperture stop of said projection display.
- 9. The projection display of claim 1 wherein said polarization compensator is built into said liquid crystal panel.
 - 10. The projection display of claim 1 wherein said polarization compensator is located at one of an entrance pupil and an exit pupil.
 - 11. The projection display of claim 1 wherein said polarization compensator is located adjacent to said15 liquid crystal panel.
 - 12. The projection display of claim 1 wherein each of said regions has electrically controlled birefringence.
 - 13. The projection display of claim 12, further comprising a feedback mechanism to adjust said birefringence of said regions.
 - 25 14. The projection display of claim 12 wherein said birefringence of said regions is adjustable over time.
 - 15. The projection display of claim 1 wherein 30 said birefringence of each of said regions is fixed.
 - 16. The projection display of claim 1, further comprising a plurality of liquid crystal panels.

₽ **L** ±

ļ.

Ė

5

10

15

20

30

comprising:

17.

- g:
 (a) providing polarized light;
- (b) generating an image from said polarized light;

A method for displaying an image,

- (c) correcting a plurality of polarization defects of said light by correcting at one location one polarization defect and correcting at another location another polarization defect where said correcting at said one location is different than said correcting at said another location, each of said locations being located in a plane that is substantially perpendicular to said light; and
- (c) projecting said image.
- 18. The method of claim 17 wherein said locations correspond to pixels.
- 19. The method of claim 18 wherein said pixels \checkmark are arranged in a rectangular matrix.
- 20. The method of claim 18 wherein said pixels are arranged concentrically.
 - 21. The method of claim 17 wherein said polarization defects are corrected at more than two locations.
 - 22. The method of claim 17 wherein said polarization defects are corrected using a transmissive liquid crystal device.

23. The method of claim 22 wherein said transmissive liquid crystal device has at least one pixel having a director orientation that is different than another director orientation of another pixel.

0/18° 5

24. The method of claim 17, further comprising transmitting said light through an analyzer, and said polarization defects are corrected before said light is transmitted through said analyzer.

10

- 25. The method of claim 17 wherein said polarization defects are corrected at an aperture stop.
- 26. The method of claim 17 wherein said
 15 polarization defects are corrected at a liquid crystal panel.
 - 27. The method of claim 17 wherein said polarization defects are corrected at one of an entrance pupil and an exit pupil.
 - 28. The method of claim 17 wherein said polarization defects are corrected at a location adjacent to a liquid crystal panel.

25

30

35

20

- 29. The method of claim 17 wherein said polarization defects are corrected by providing a polarization compensator having a plurality of pixels each having a respective birefringence, said birefringence of one of said pixels being is different than said birefringence of another of said pixels.
- 30. The method of claim 29, further comprising electronically controlling said birefringence of said pixels.

5

- 32. The method of claim 17 wherein said polarization defects are corrected at different times.
- 33. The method of claim 27 wherein said 10 birefringence of each of said pixels is fixed.

The Comment of the Co